

**Section 1: IDENTIFICATION**

**Product Name:** Void & Rudder Float Coat

**Synonyms:** Not available.

**Product Use:** Rust and corrosion inhibitor for marine environments.

**Restrictions on Use:** Not available.

**Manufacturer/Supplier:** Ship-2-Shore  
109-7337 North Fraser Way  
Burnaby, BC V5J 0G7  
Canada

**Phone Number:** 800-430-1533

**Emergency Phone:** For Hazardous Materials [or Dangerous Goods] Incident  
Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC  
1-800-424-9300 / +1 703-527-3887 CCN 991123

**Date of Preparation of SDS:** May 10, 2021

**Section 2: HAZARD(S) IDENTIFICATION**

**GHS INFORMATION**

**Classification:** Flammable Liquids, Category 4  
Skin Irritation, Category 2

**LABEL ELEMENTS**

**Hazard**

**Pictogram(s):**



**Signal Word:** Warning

**Hazard Statements:** Combustible liquid.  
Causes skin irritation.

**Precautionary Statements**

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wash hands thoroughly after handling.  
Wear protective gloves, protective clothing and eye protection.

**Response:** IF ON SKIN: Wash with plenty of water.  
If skin irritation occurs: Get medical attention.  
Take off contaminated clothing and wash it before reuse.  
In case of fire: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam to extinguish.

**Storage:** Store in a well-ventilated place. Keep cool.



SAFETY DATA SHEET

Void & Rudder Float Coat

Date of Preparation: May 10, 2021

Disposal: Dispose of contents and container in accordance with applicable regional, national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: 65% of this product mixture consists of ingredient(s) of unknown acute toxicity.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200).

This material is considered hazardous by the Hazardous Products Regulations.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Table with 4 columns: Ingredient(s), Common name / Synonyms, CAS No., % wt./wt. Rows include Distillates (petroleum), solvent-dewaxed heavy paraffinic; Distillates (petroleum), hydrotreated heavy paraffinic; Distillates (petroleum), hydrotreated light; Stoddard solvent; Proprietary Additive Mixture.

Section 4: FIRST-AID MEASURES

Inhalation: If inhaled: Call a poison center or doctor if you feel unwell. Acute and delayed symptoms and effects: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness. Eye Contact: If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center or doctor if you feel unwell. Acute and delayed symptoms and effects: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Skin Contact: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin irritation occurs: Get medical attention. Wash contaminated clothing before reuse. Acute and delayed symptoms and effects: Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching. Ingestion: If swallowed: Call a poison center or doctor if you feel unwell. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

**Acute and delayed symptoms and effects:** May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

**Note to Physicians:** Symptoms may not appear immediately.

### Section 5: FIRE-FIGHTING MEASURES

**FLAMMABILITY AND EXPLOSION INFORMATION**

Combustible liquid. Will be ignited by heat, sparks or flames. Vapor explosion hazard indoors, outdoors or in sewers. Containers may explode when heated.

**Sensitivity to Mechanical Impact:** This material is not sensitive to mechanical impact.

**Sensitivity to Static Discharge:** This material is sensitive to static discharge.

**MEANS OF EXTINCTION**

**Suitable Extinguishing Media:** Small Fire: Dry chemical, CO<sub>2</sub>, water spray or regular foam.

Large Fire: Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.

**Unsuitable Extinguishing Media:** Not available.

**Products of Combustion:** Oxides of carbon.

**Protection of Firefighters:** Fire may produce irritating, corrosive and/or toxic gases. Runoff from fire control or dilution water may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

### Section 6: ACCIDENTAL RELEASE MEASURES

**Emergency Procedures:** Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

**Personal Precautions:** Do not touch or walk through spilled material. Use personal protection recommended in Section 8.

**Environmental Precautions:** Keep out of drains, sewers, ditches, and waterways.

**Methods for Containment:** Stop leak if without risk. Contain spill and absorb with inert absorbent. Large pools may be covered with foam to prevent vapour evolution. Do not flush to sewer or allow to enter waterways.

**Methods for Clean-Up:** Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking

tools to collect absorbed material. Large spills should be removed with explosion proof vacuum equipment.

**Other Information:** See Section 13 for disposal considerations.

### Section 7: HANDLING AND STORAGE

**Handling:**

Do not swallow. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Wash hands thoroughly after handling. See Section 8 for information on Personal Protective Equipment.

**Storage:**

Store in a well-ventilated place. Keep cool. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.

### Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Guidelines**

**Component**

Distillates (petroleum), solvent-dewaxed heavy paraffinic [CAS No. 64742-65-0]

**ACGIH:** Exposure by all routes should be carefully controlled to levels as low as possible (2009); For Mineral oil, excluding metal working fluids; Poorly and mildly refined

**OSHA:** 5 mg/m<sup>3</sup> (TWA); For Oil mist, mineral.

Distillates (petroleum), hydrotreated heavy paraffinic [CAS No. 64742-54-7]

**ACGIH:** Exposure by all routes should be carefully controlled to levels as low as possible (2009); For Mineral oil, excluding metal working fluids; Poorly and mildly refined

**OSHA:** 5 mg/m<sup>3</sup> (TWA); For Oil mist, mineral.

Distillates (petroleum), hydrotreated light [CAS No. 64742-47-8]

**ACGIH:** 100 ppm (TWA); (1980); For Stoddard solvent

**OSHA:** 500 ppm (TWA), 2900 mg/m<sup>3</sup> (TWA); For Stoddard solvent.  
100 ppm (TWA) [Vacated]; For Stoddard solvent.

Stoddard solvent [CAS No. 8052-41-3]

**ACGIH:** 100 ppm (TWA); (1980);

**OSHA:** 500 ppm (TWA), 2900 mg/m<sup>3</sup> (TWA);  
100 ppm (TWA) [Vacated];

Proprietary Additive Mixture [CAS No. Not available.]

**ACGIH:** No TLV established.

**OSHA:** No PEL established.

**PEL:** Permissible Exposure Limit

**TLV:** Threshold Limit Value

**TWA:** Time-Weighted Average

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapour, gas, etc.) below

recommended exposure limits. Use explosion-proof electrical, ventilating, and lighting equipment.

**PERSONAL PROTECTIVE EQUIPMENT (PPE)**



- Eye/Face Protection:** Wear safety glasses with side shields. Use equipment for eye protection that meets the standards referenced by CSA Standard CAN/CSA-Z94.3 and OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.
- Hand Protection:** Wear protective gloves. For occasional contact wear standard disposable nitrile or Viton gloves. For extended exposure wear Neoprene gloves.
- Skin and Body Protection:** Wear protective clothing.
- Respiratory Protection:** Not normally required. If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4, with organic vapor cartridge, or self-contained breathing apparatus must be used.
- General Hygiene Considerations:** Handle according to established industrial hygiene and safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.

**Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance:** Brown liquid.
- Colour:** Brown.
- Odour:** Petroleum.
- Odour Threshold:** Not available.
- Physical State:** Liquid.
- pH:** Not available.
- Melting Point / Freezing Point:** Not available.
- Initial Boiling Point:** Not available.
- Boiling Range:** Not available.



SAFETY DATA SHEET

**Void & Rudder Float Coat**

Date of Preparation: May 10, 2021

<b>Flash Point:</b>	78 °C (172.4 °F) (ASTM D93)
<b>Evaporation Rate:</b>	Not available.
<b>Flammability (solid, gas):</b>	Not applicable.
<b>Lower Flammability Limit:</b>	Not available.
<b>Upper Flammability Limit:</b>	Not available.
<b>Vapor Pressure:</b>	Not available.
<b>Vapor Density:</b>	Not available.
<b>Relative Density:</b>	0.883 (Water = 1) at 15.6 °C (60.1 °F)
<b>Solubilities:</b>	Soluble in water.
<b>Partition Coefficient: n-Octanol/Water:</b>	Not available.
<b>Auto-ignition Temperature:</b>	Not available.
<b>Decomposition Temperature:</b>	Not available.
<b>Viscosity:</b>	80 cSt at 40 °C (104 °F)
<b>Percent Volatile, wt. %:</b>	9.96
<b>VOC content, wt. %:</b>	0.7 lb/gal
<b>Density:</b>	884.5 kg/m <sup>3</sup>
<b>Coefficient of Water/Oil Distribution:</b>	Not available.

**Section 10: STABILITY AND REACTIVITY**

<b>Reactivity:</b>	Contact with incompatible materials. Sources of ignition. Exposure to heat.
<b>Chemical Stability:</b>	Stable under normal storage conditions.
<b>Possibility of Hazardous Reactions:</b>	None known.
<b>Conditions to Avoid:</b>	Contact with incompatible materials. Sources of ignition. Exposure to heat.
<b>Incompatible Materials:</b>	Strong oxidizers.
<b>Hazardous Decomposition Products:</b>	Not available.

**Section 11: TOXICOLOGICAL INFORMATION**

**EFFECTS OF ACUTE EXPOSURE**

**Product Toxicity**

**Oral:** Not available.

**SAFETY DATA SHEET****Void & Rudder Float Coat**

Date of Preparation: May 10, 2021

**Dermal:** Not available.**Inhalation:** Not available.**Component Toxicity**

<b>Component</b>	<b>CAS No.</b>	<b>LD<sub>50</sub> oral</b>	<b>LD<sub>50</sub> dermal</b>	<b>LC<sub>50</sub></b>
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	> 5000 mg/kg (rat)	> 5000 mg/kg (rabbit)	Not available.
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	> 15000 mg/kg (rat)	> 5000 mg/kg (rabbit)	Not available.
Distillates (petroleum), hydrotreated light Stoddard solvent	64742-47-8	Not available.	Not available.	Not available.
Proprietary Additive Mixture	8052-41-3	Not available.	Not available.	Not available.
	Not available.	Not available.	Not available.	Not available.

**Likely Routes of Exposure:** Eye contact. Skin contact. Inhalation. Ingestion.**Target Organs:** Skin. Eyes. Gastrointestinal tract. Respiratory system. Kidneys. Central nervous system.**Symptoms (including delayed and immediate effects)****Inhalation:** May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness.**Eye:** May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.**Skin:** Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching.**Ingestion:** May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.**Skin Sensitization:** Not available.**Respiratory Sensitization:** Not available.**Medical Conditions Aggravated By Exposure:** Not available.



**SAFETY DATA SHEET**

**Void & Rudder Float Coat**

Date of Preparation: May 10, 2021

**EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)**

- Target Organs:** Skin. Eyes. Gastrointestinal tract. Respiratory system. Blood. Bone marrow. Liver. Kidneys. Central nervous system. Lymphoid tissue.
- Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation.
- Carcinogenicity:** This product does not contain any carcinogens or potential carcinogens above reportable thresholds as listed by ACGIH, IARC, OSHA, or NTP.
- Mutagenicity:** Not available.
- Reproductive Effects:** Not available.
  
- Developmental Effects**
  - Teratogenicity:** Not available.
  - Embryotoxicity:** Not available.
- Toxicologically Synergistic Materials:** Not available.

**Section 12: ECOLOGICAL INFORMATION**

- Ecotoxicity:** Not available.
- Persistence / Degradability:** Not available.
- Bioaccumulation / Accumulation:** Not available.
- Mobility in Environment:** Not available.
- Other Adverse Effects:** Not available.

**Section 13: DISPOSAL CONSIDERATIONS**

- Disposal Instructions:** Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

**Section 14: TRANSPORT INFORMATION**

**U.S. Department of Transportation (DOT)**

- Proper Shipping Name:** Not regulated. Product does not sustain combustion, as per ASTM D4206 testing.
- Class:** Not applicable.
- UN Number:** Not applicable.
- Packing Group:** Not applicable.
- Placard(s):** Not applicable.

**Canada Transportation of Dangerous Goods (TDG)**

- Proper Shipping Name:** Not regulated.
- Class:** Not applicable.





SAFETY DATA SHEET

Void & Rudder Float Coat

Date of Preparation: May 10, 2021

UN Number: Not applicable.

Packing Group: Not applicable.

Placard(s): Not applicable.

Section 15: REGULATORY INFORMATION

Chemical Inventories

US (TSCA)

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

Federal Regulations

United States

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA Title III

No components are listed.

State Regulations

Massachusetts

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

Component	CAS No.	RTK List
Distillates (petroleum), hydrotreated light	64742-47-8	Listed.
Stoddard solvent	8052-41-3	Listed.

New Jersey

US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

Component	CAS No.	RTK List
Distillates (petroleum), hydrotreated light	64742-47-8	Listed.
Stoddard solvent	8052-41-3	Listed.

Pennsylvania

US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Component	CAS No.	RTK List
Distillates (petroleum), hydrotreated light	64742-47-8	Listed.
Stoddard solvent	8052-41-3	Listed.

California

California Prop 65: This product does not contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Section 16: OTHER INFORMATION

Disclaimer:



**SAFETY DATA SHEET**

**Void & Rudder Float Coat**

Date of Preparation: May 10, 2021

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

**Date of Preparation of SDS:** May 10, 2021

**Version:** 1.0

**GHS SDS Prepared by:** Deerfoot Consulting Inc.

**Phone:** (403) 720-3700